
Portable agentic phenomenology



CSU HEPPA Seminar

September 1st, 2026

Based on 2512.15867, 2603.26990, 2609.00107, 2609.xxxx

Tony Menzo, PhD

Joint postdoc @ Fermilab and the University of Alabama

Outline

1. What are **tools**, **agents, harnesses** etc.
2. Status of the field (the “zoo”)
3. Toward portable/cumulative/reproducible agent science in HEP (**the *HEPTABench* stack**)
   - HEPTAPOD, toolbase, toolbench, hepbench
4. Toward autonomous pheno … ?
5. Conclusions

Why?

Modern frontier large-language-models (LLMs) are

- **pretty reliable compressions** of human knowledge (proto-AGI)
- generic computational interfaces, becoming **very** powerful assistants
- evolving rapidly

Useful for science? HEP-(ph,th,ex)?

- **Extending/amplifying thinking**
- **Facilitation & automation (off-load tasks)**
- **Assistance (enhance accessibility)**

Why?

Since ~November/December of last year (2025) there has been a "Cambrian explosion" of papers demonstrating the use of agents in HEP.

[Submitted on 23 Mar 2026]
The FERMIACC: Agents for Particle Theory
Prateek Agrawal, Nathaniel Craig, Amalia Ma

[Submitted on 5 Mar 2026 (v1), last revised 26 Mar 2026 (this version, v2)]
Agentic AI -- Physicist Collaboration

[Submitted on 2 Oct 2025]
ArgoLOOM: agentic AI for fund from quarks to cosmos
S. D. Bakshi, P. Barry, C. Bissolotti, I. Cloet, S. C

[Submitted on 20 Apr 2026 (v1), last revised 1 Jul 2026 (this version, v2)]
A Scientific Human-Agent Reproduction Pipeline
Joschka Birk, Gregor Kasieczka, Siddharth Mi
Nachman, Dennis Noll, Tanvi Wamorkar

[Submitted on 30 Jun 2026]
EasyScan_HEP 2: Agent-Ready Parameter Scans for High-Energy Physics

[Submitted on 17 Jun 2026]
LeWRON: Agentic Analysis of Electroweak Phase Transitions

[Submitted on 16 Apr 2026]
Development of an LLM-Based System for
Code Generation from

[Submitted on 23 Apr 2026 (v1), last revised 18 Jun 2026 (this ve
Agentic-AI Detector Co-design Optimization in

[Submitted on 19 Feb 2025]
Theoretical Physics Benchmark (TPBench) -- a Dataset and Study of AI Reasoning Capabilities
Li, Moritz Münchmeyer,

[Submitted on 17 Dec 2025 (v1), last revised 18 Jul 2026 (this version, v2)]
HEPTAPOD: Orchestrating High Energy Physics Workflows Towards Autonomous Agency
Tony Menzo, Al
George T. Flem

[Submitted on 27 Mar 2026]
Agentic Diagrammatica: Towards Symbolic Computation in High Energy

[Submitted on 9 Jun 2026 (v1), last revised 27 Jul 2026 (this version, v2)]
DarkAgents
Michele Lucente,

[Submitted on 24 Apr 2026]
Dr.Sai: An agentic AI for real-world physics analysis at BESIII
unkun Jiao, Mingrun Li, Ke Li, Yipu Liao, Beijiang

[Submitted on 3 Jun 2026]
Archi: Agentic Operations at the CMS Experiment
Pietro Lugato, Luca Lavezzo, Jason Mohoney, Hasan Ozturk, Muhammad

[Submitted on 22 Dec 2025 (v1), last revised 13 Aug 2026 (this version, v2)]
PhysMaster: Building an Autonomous AI Physicist for Theoretical and Computational Physics Research
Tingjia Mi
Yuwen Du

[Submitted on 13 May 2026]
Collider-Bench: Benchmarking AI Agents with Particle Phy
Darius A. Farough
Sharma, David Shi

[Submitted on 24 Jul 2026]
SMEFT-Pheno-Agent: a natural-language-driven AI agent for machine-learning-assisted Standard Model Effective Field T

[Submitted on 7 Jul 2026]
Articulating Assumptions in AI-Generated Scientific Analyses through Task Decomposition
Ahmed Hammad, Mihoko Nojiri

[Submitted on 11 Jun 2026 (v1), last revised 23 Jun 2026 (this version, v3)]
AgentRivet: an automated system for producing Rivet routines from journal publications
Antonio J. Costa, Caterina Doglioni, Christian Gütschow, Andrew D. Pilkington, Sukanya Sinha

[Submitted on 31 Jan 2026]
GRACE: an Agentic AI for Particle Physics Experiment Design and Simulation
Justin Hill,

[Submitted on 14 Jul 2026]
Scattering Amplitudes as Programs: Self-Evolving Search for Theory and Event Generation

[Submitted on 8 Dec 2025]
Automating High Energy Phy with LLM-
Eli Gendreau-Dist
Haichen Wang, Ch

[Submitted on 17 May 2026 (v1), last revised 18 May 2026 (this version, v2)]
RooAgent: Energy Phy
Aman Desai

[Submitted on 30 Oct 2023 (v1), last revised 14 Jun 2025 (this version, v3)]
CoLLM: Integrating Collaborative Em into Large Language Models for Recommendation
Yang Zhang, Fuli Feng, Jizhi Zhang, Keqin Bao, Qifan Wang, Xianghan He


[Submitted on 15 Mar 2026]
An End-to-end Architecture for Collider and Beyond
Shi Qiu, Zeyu Cai, Jiashen We
Liu, Ming-xing Luo, Xing-Bo

[Submitted on 28 Jan 2026 (v1), last revised 5 Aug 2026 (this versio
MadAgents
Tilman Plehn, Daniel Schiller, Nikita Schmal

[Submitted on 16 Jul 2026]
LQCDMaster: Agentic Scientific Computing for Lattice Quantum
Haofei Gao, Tingjia Miao,
Ran, Jinxin Tan, Zhentao
Qi-An Zhang, Siheng Che

[Submitted on 24 Jul 2026]
Agentic Re-Casting using Agentic Re-Simulations
Sascha Diefenbacher, Tilman Plehn, Daniel Schiller, Nikita Schmal


A Cambrian explosion of AI agents in high-energy physics



hep-ph / hep-ex / hep-lat / hep-th, binned by arXiv announcement month, through 28 Aug 2026. Hand-curated from a full-text query on LLM / agent / autonomy terms; excludes reinforcement-learning "agents" and foundation models.

Goal (for me)

Research assistant!
(We'll come back what I mean by this later)









Large language models (LLMs)

A parameterized function that represents a **conditional probability distribution over discrete actions**, where the primitive action is emitting the next token.

$$p_\theta(x_{t+1} \mid x_{\leq t})$$

Learned parameters **Next token** **Context**






Frontier models have 10^{11}-10^{12} parameters


***LLMs are inherently stochastic**

“The Road to ~~Homo Sapiens~~ Agents”

1. Collect and filter ~the internet
2. Pre-train → base model
3. Post-train → assistant
   - Alignment
   - **Tool calling is introduced**



Pre-trained base model



Post-trained “assistant”

What is a tool?

To an LLM, a **tool** is a **function:**

```
output = tool(input)
```

where the **model generates the input** in a structured form and **receives output back in its context.**

User


What's the weather in Tokyo?

What is a tool?

To an LLM, a **tool** is a **function:**

```
output = tool(input)
```

where the **model generates the input** in a structured form and **receives output back in its context.**



What is a tool?

To an LLM, a **tool** is a **function:**

```
output = tool(input)
```

where the **model generates the input** in a structured form and **receives output back in its context.**

Agent


```
<|start|>assistant<|channel|>commentary
to=functions.get_weather
<|constrain|>json<|message|>{"city":"Tokyo"}<|call|>
```

“The Road to ~~Homo Sapiens~~ Agents”


3. Post-train → assistant
4. Post-train with (base) tools

(ReadFile, EditFile, Glob, …)


- LLM can now act as a computer interface



Pre-trained base model




“LLM computer”




Post-trained “assistant”

“The Road to ~~Homo Sapiens~~ Agents”


4. Post-train with (base) tools
5. Trap in isolated sandbox with tools → **Agent**




Pre-trained base model



Agent



“LLM computer”




Post-trained “assistant”

What is an agent?

Given ***context*** C_t at a decision step t, and an ***action*** $\mathscr{A}_t$ selected from and action space $\mathscr{A}$, an ***agent*** is a system that implements a conditional distribution over actions:


$$p(\mathscr{A}_t \,|\, C_t)$$

and is embedded in a feedback loop such that executed actions influence future context.



“I’m not seeing Armageddon here.”


5. Trap in isolated sandbox with tools → **Agent**
6. Custom tools and prompts, allow for users to ***steer agent behavior to accomplish arbitrary long- or short-horizon tasks***



An **agentic harness** is the system of prompts, tools, schemas, and execution environments that harnesses an LLM’s flexible intelligence while constraining it into reliable, reproducible, user-directed action.

“I’m not seeing Armageddon here.”

5. Trap in isolated sandbox with tools → **Agent**
6. Custom tools and prompts, allow for users to ***steer agent behavior to accomplish arbitrary long- or short-horizon tasks***




An **agentic harness** is the system of prompts, tools, schemas, and execution environments that harnesses an LLM’s flexible intelligence while constraining it into reliable, reproducible, user-directed action.

Harness engineering a.k.a “agentic programming”

Using **LLM agents** to solve problems with an explicit **closed-loop decision process**, where behavior is specified through structured prompting, tools (a harness). The harness induces a constrained conditional action distribution

$$p(\mathcal{A}_t \mid C_t) \to p_h(\mathcal{A}_t \mid C_t).$$

“New programming paradigm”



Harness engineering

Traditional programming

- Specify ***how*** to do something.
- Scripting.
- Control flow is explicit and tractable.

Agentic programming

- Specify ***what*** you want accomplished.
- Context engineering.
- Control flow is emergent and ***non-deterministic.***

The biggest shift is moving from **engineering** certainty to **managing uncertainty** (and where you want it).

Harness design

Agent interaction “modalities”

The burden of verification
(when, where, how much)

Assistance	versus	**Automation**
Researcher chooses directions, inspects intermediate results, and redirects work. Inherently “turn-by-turn”.		Bounded workflow that runs without human review because its decisions, validation rules, stopping conditions, etc. were engineered in advance.

***Not mutually exclusive**

Harness design

Goal **(refined)**

How much can be automated, and with what degree of **reliability**?

What is the class of problems the will eventually be automatable?

Automate these tasks!

f verification
re, how much)

sus

researcher chooses directions, inspects intermediate results, and redirects work. Inherently “turn-by-turn”.


Automation

Bounded workflow that runs without human review because its decisions, validation rules, stopping conditions, etc. were engineered in advance.

****Not mutually exclusive***

Harness design in HEP (the “zoo”)

A taxonomy



There are currently **~40 HEP(-ph,-ex,-th)** specific systems “on the market”.

They admit a nice classification w.r.t the structure of the interface exposed to the agent.

Harness design in HEP (the “zoo”)

A taxonomy

Free-form

Agent produces executable behavior directly through unconstrained code or command generation; domain context can guide it, but no fixed interface determines what operations it can express.

	Name	Architecture	MCP	Multi-agent	Domain / role
Free-form	MadAgents [4]	Free-form code generation	–	✓	Collider phenomenology
	HEP Data Analysis Agents [7]	Free-form generation in fixed workflow DAG	–	✓	Experimental analysis
	JFC [1]	Free-form generation, literature-grounded	–	✓	Experimental analysis
	CoLLM [8]	Free-form generation, structured prompt	–	✗	Collider DL analysis
	PhysMaster [9, 10]	Free-form generation, validated-trace memory	–	✓	Theory / lattice QCD
	Agents of Discovery [5]	Free-form code generation	–	✓	New-physics analysis
	ArgoLOOM [2]	Orchestrated module wrappers, RAG-grounded	–	✓	Cosmology, collider, nuclear
	ALEPH thrust [3]	Free-form generation, physicist-directed	–	✗	Experimental analysis
	SFitter Agents [6]	Orchestrator with consultant agents	–	✓	Global SMEFT re-casting
	CLVisc Agent [23]	Free-form execution, agent-authored skill	–	✗	Heavy-ion hydrodynamics
	Amplitude program search [35]	Coding agent in generate–evaluate–select loop	–	✗	Scattering amplitudes
	Detector co-design [36]	Agentic loop over bi-level optimizer	–	✗	Detector design

The burden of verification:

When?	Who/Where?	Per-run burden
After or during every generated implementation	Human	Highest

Harness design in HEP (the “zoo”)

A taxonomy

Structured-handoffs

Agent generates implementations freely, but the intermediate artifacts exchanged between agents or workflow stages must follow a prescribed format or schema.

	Name	Architecture	MCP	Multi-agent	Domain / role
Structured handoffs	Dr. Sai [11]	Role agents over experiment software	–	✓	Experimental analysis
	DarkAgents [12]	Sub-agents with JSON handoff contracts	–	✓	Astroparticle / dark sectors
	SHARP [13]	Machine-readable project spec, subagents	–	✓	Analysis reproduction
	AgentRivet [14]	Provider-agnostic agents, output schemas	–	✓	Analysis preservation
	Semantic differencing [15]	Multi-agent trace and critique of generated code	–	✓	Analysis audit
	Selection-list codegen [16]	Structured selection list between stages	–	✓	Analysis reproduction
	LQCDMaster [17]	Hybrid: skill-guided generation, deterministic Wick tool	–	✓	Lattice QCD

The burden of verification:

When?	Who/Where?	Per-run burden
After or during every generated implementation	Handoff validators, Human	High

Harness design in HEP (the “zoo”)

A taxonomy

Configuration/DSL mediated

	Name	Architecture	MCP	Multi-agent	Domain / role
Fixed backend	ColliderAgent [18]	CLI/template-mediated	✓	✓	Collider phenomenology
	HepScript [19]	Constrained-grammar DSL	–	✗	Experimental analysis
	EasyScan_HEP 2 [20]	Agent-written configuration, fixed backend	–	✗	Parameter scans
	SMEFT-Pheno-Agent [21]	Locked configuration, phase manifests	–	✗	SMEFT phenomenology

Agent specifies a workflow using a bounded configuration language, template, command interface, or domain-specific-language, which a fixed backend interprets and executes.

The burden of verification:

When?	Who/Where?	Per-run burden
Mainly when backend/ DSL is authored, then when each spec is produced	Fixed backend, parser	Moderate

Harness design in HEP (the “zoo”)

A taxonomy

Tool-constrained

The agent selects and composes discrete, fixed, versioned scientific operations through structured invocation structure.


	Name	Architecture	MCP	Multi-agent	Domain / role
Valid-by-rejection	RooAgent [25]	Typed tool registry over LangGraph and MCP	✓	✗	Experimental analysis
	FERMIACC [24]	Typed schemas over a guarded pipeline	–	✓	Particle theory
	GRACE [26]	Tool-invocation DAG; value-level verification against physics constraints	–	✗	Detector / experiment design
	bsm-agent [27]	Tool calling over a symbolic backend	–	✗	BSM model building
	LeWRON [33]	Audited toolbox with auditor agents	–	✓	Particle cosmology
	Archi [34]	ReAct agent over corpus and live MCP tools	✓	✗	Experimental operations
Valid-by-construction	HEPTAPOD (event generation) [31]	Typed schema constrains decoding	✓	✗	Collider phenomenology
	HEPTAPOD (Diagrammatica) [32]	Typed schema constrains decoding	✓	✗	Symbolic computation

The burden of verification:

When?	Who/Where?	Per-run burden
Tool authoring and each invocation/ composition	Tool selection/ arguments, tool call validator	Low

Harness design in HEP (the “zoo”)


A phase diagram



*Other relevant axes, $/token, $/performance, tokens/performance, generation time, etc.

Harness design in HEP (the “zoo”)

A phase diagram



*Other relevant axes, $/token, $/performance, tokens/performance, generation time, etc.

Where are these boundaries? How can they be determined systematically?


Testing the harness

“Is this thing on?”


Benchmarks!

Naive minimal spec:

- **Task + task scaffolding**
  - Sandbox and workspace initialization, system prompt, etc.



- **Rubric**
  - Final expected outcome. Grading: binary or continuous, stage-by-stage grading




Testing the harness

"Is this thing on?"

LLMs are distributions!

Agents trajectory/final result should be treated as a random variable with mean and variance (when applicable).




Testing the harness

"Is this thing on?"

What can influence an agents trajectory?


The "6-sphere"



Benchmarking in HEP

Name	Scope	Grading	Integrity control / retained evidence
Collider-Bench [22]	LHC analysis reproduction; 10 tasks from 4 papers	Histogram fidelity, no hand-written rubric; 3 repeats; cost reported	LLM judge audits workspace and session trace for fabrication
TPBench [37]	HEP theory and cosmology; 57 problems	Automated numeric verification; holistic grading of reasoning	Public/private split maintained against leakage
CritPt [38]	Frontier physics research incl. HEP; 71 challenges, 190 checkpoints	Physics-format-aware auto-grading; reliability metric; cost reported	Unpublished problems, guess-resistant by construction
PRL-Bench [39]	End-to-end physics research; 100 papers across 5 subfields	Objective verifiability; expert-validated tasks	Published-source tasks; retained execution evidence not specified


Each of these benchmarks only operate at a single point in the 6-sphere



Benchmarking in HEP

Name	Scope	Grading	Integrity control / retained evidence
Collider-Bench [22]	LHC analysis reproduction; 10 tasks from 4 papers	Histogram fidelity, no hand-written rubric; 3 repeats; cost reported	LLM judge audits workspace and session trace for fabrication
TPBench [37]	HEP theory and cosmology; 57 problems	Automated numeric verification; holistic grading of reasoning	Public/private split maintained against leakage
CritPt [38]	Frontier physics research incl. HEP; 71 challenges, 190 checkpoints	Physics-format-aware auto-grading; reliability metric; cost reported	Unpublished problems, guess-resistant by construction
PRL-Bench [39]	End-to-end physics research; 100 papers across 5 subfields	Objective verifiability; expert-validated tasks	Published-source tasks; retained execution evidence not specified

It would be ideal to scan larges parts of this space easily



Status of agents in HEP

Bottom line – it's the Wild West, as expected

As with all new fields of research, community standards are lagging behind.

Initial systems/demonstrations are promising, but hard to reuse and reproduce results without significant effort.


Initial benchmarks are also great, but again, reproducibility is an issue.

A cohesive framework is lacking.

Infrastructure mode… engage



Zoo




Ecosystem

Infrastructure for a community-driven HEP harness

Utilize and adapt existing infrastructure as much as possible!
General purpose coding harnesses + domain tools & skills = HEP agent


- **Adopt a standard protocol for interfacing tools with harnesses**
  - **Model Context Protocol (MCP)** has been widely adopted by all harnesses, let's not reinvent the wheel!
- **Community maintained registry/tool-skill database + serving**
  - Scalable — what do you do when you have $\mathcal{O}(1000)$ tools to choose from? Need easy curation of custom "loadouts"
- **Science-forward benchmarking framework**
  - Emphasis on reproducibility and full "6-sphere" resolution



Infrastructure for a community-driven HEP harness

An implementation: “the stack”


- Adopt a standard protocol for interfacing tools with harnesses
  - MCP
- Community maintained registry/ tool-skill database + serving
  - toolbase
- Science-forward benchmarking framework
  - toolbench, hepbench
- Toolkit
  - heptapod



Infrastructure for a community-driven HEP harness

An implementation: “the stack”

- Adopt a standard protocol for interfacing tools with harnesses
  - MCP
- Community maintained registry/ tool-skill database + serving
  - toolbase
- Science-forward benchmarking framework
  - toolbench, hepbench
- Toolkit
  - heptapod



HEPTAPOD


https://github.com/tonymenzo/heptapod


60+ tools/skills

#	Tool
Event generation and simulation	
1	FeynRulesToUFOTool
2	MadGraphFromRunCardTool
3	PythiaFromRunCardTool
4	SherpaFromRunCardTool
5	JetClusterSlowJetTool
Event-format conversion and arra	
6	LHEToJSONLTool
7	EventJSONLToNumpyTool
8	JetsJSONLToNumpyTool
Kinematic analysis and event sele	
9	CalculateInvariantMassTool
10	CalculateTransverseMomentumTool
11	CalculateDeltaRTool
12	ApplyCutsTool
13	GetHardestNTool
14	GetHardestNJetsTool
15	FilterByPDGIDTool
16	SortByPtTool
17	MergeObjectCollectionsTool
18	FilterByDeltaRTool
Resonance reconstruction	
19	ResonanceReconstructionTool
Diagrammatica / exact symbolic tools	
20	ComputeSymbolicAmplitudeTool
21	RunWolframTool
22	RunWolframScriptBatch
23	SimplifyResultTool
24	ConvertToPythonTool
NDA and FeynGraph	
25	EstimateDecayWidthNDATool
26	EstimateBranchingRatioNDATool
27	EnumerateDiagramsTool
28	DiagramVisualizationTool
PDG and INSPIRE tools	
29	PDGDatabaseTool
30	PDGSearchTool
31	PDGPropertyTool
32	InspireSearchTool
33	InspirePaperTool
34	InspireCitationTool
35	InspireBibTeXTool
36	InspireAuthorTool
37	InspireInstitutionTool
38	InspireConferenceTool
39	InspireJournalTool
40	InspireExperimentTool
41	InspireReadingListTool
42	InspireNotesTool


Example(s)

Event generation ($\mathscr{L} \to \mathcal{O}$)





Task: From $\mathscr{L} \to$



Task scaffold:

System

```
.
├── feynrules
│   └── models
│       └── S1_LQ_RR.fr
├── madgraph
│   └── cards
│       └── S1_LQ_RR_pp_lqlq_scan.mg5
└── pythia
    └── cards
        └── S1_LQ_RR_pp_ljlj.cmnd

7 directories, 3 files
```


Rubric:


Stage	Wt.	Passes when the run has produced...
UFO model	0.10	a valid UFO model directory (particle, parameter, vertex, and coupling modules).
Parton events	0.15	≥ 100 parton-level events (LHE) across the parameter scan.
Showering	0.10	≥ 100 per-event showered-particle records.
Jet clustering	0.10	≥ 100 per-event clustered-jet records.
Reconstruction	0.05	≥ 50 reconstructed $m_{\rm LQ}^{\rm min}$ values.
Correct mass	0.50	an $m_{\rm LQ}^{\rm min}$ distribution peaking at all three injected scan masses (1000, 1500, 2000 GeV) within 10%, together with a plotted deliverable.

Example(s)

Event generation ($\mathscr{L} \to \mathcal{O}$)

Task: From $\mathscr{L}$ →





FeynRules

model.fr

$\mathcal{L} \supset y_{ij}\, \overline{u_i^c}\, \ell_j\, S_1^\dagger + \text{h.c.}$

$S_1 \sim (\bar{\mathbf{3}}, \mathbf{1}, -1/3)$

MG5

mod

r

User

Plan a Monte Carlo signal-validation analysis of the BSM scalar leptoquark defined by the supplied run cards. Generate 10,000 events, select objects, and create lepton-jet invariant-mass distributions for each parameter point. Attempt to isolate and reconstruct the leptoquark resonance by applying reasonable lepton-jet separation and experimental cuts. Compute and plot the resulting $m_{\rm LQ}^{\rm min}$ distribution. Write a todo list first and then execute the todo list until completed.

lqlq_scan.mg5

ljlj.cmnd

7 directories, 3 files


Rubric:


Stage	Wt.	Passes when the run has produced...
UFO model	0.10	a valid UFO model directory (particle, parameter, vertex, and coupling modules).
Parton events	0.15	≥ 100 parton-level events (LHE) across the parameter scan.
Showering	0.10	≥ 100 per-event showered-particle records.
Jet clustering	0.10	≥ 100 per-event clustered-jet records.
Reconstruction	0.05	≥ 50 reconstructed $m_{\rm LQ}^{\rm min}$ values.
Correct mass	0.50	an $m_{\rm LQ}^{\rm min}$ distribution peaking at all three injected scan masses (1000, 1500, 2000 GeV) within 10%, together with a plotted deliverable.

Example(s)

Event generation ($\mathscr{L} \to \mathscr{O}$)

Model: gpt-oss-120b






Domain tools improve gpt-oss-120b's pass rate from 0/10→7/10

An example

Forward LLP reach estimate




Muon-philic scalar

Task: $\mathscr{L}$, $\mathscr{I} \equiv \{\sqrt{s}, \sigma_{\text{inel}}, N_{\text{int}}, \theta_{\max}, N_{\text{target}}\}$, $\mathscr{G} \equiv \{z_{\text{prod}}, z_{\min}, z_{\max}, R, z_{\text{det}}, R_{\text{det}}, x_{\text{off}}\}$

Task scaffold: ~None

Rubric:

Stage and configuration ID	w_m	Credit and graded evidence
Valid answer and scan `answer_present`	0	Required fields in `results/answer.json` and a populated `results/scan.csv`.
Forward-flux artifact `pythia_ran`	0	Presence of a flux-related artifact; retained as a diagnostic rather than scientific credit.
Widths and lifetime `width_correct`	0.10	Binary check of the dimuon formula, dimuon and diphoton width probes, lifetime probes, and g^{-2} scaling.
Channel coverage `channels_present`	0.10	Fraction of reference-reached search–mass points through $m_\phi = 0.70\,\text{GeV}$ supplied with nonzero yields.
Signal-yield accuracy `yield_distance`	0.40	Continuous credit $10^{-D_{N_{\text{sig}}}}$ over the 48 declared (search, m_ϕ, g) evaluation points.
Lower contour edge `contour_lower`	0.15	Continuous credit $10^{-D_{g_{\text{lower}}}}$ for the production-limited sensitivity boundary.
Upper contour edge `contour_upper`	0.15	Continuous credit $10^{-D_{g_{\text{upper}}}}$ for the lifetime-limited sensitivity boundary.
False reach `no_spurious_reach`	0.05	Fraction of reference-insensitive points for which no sensitivity is reported.
Exclusion figure `reach_plot`	0.05	Fraction of required plotting criteria satisfied, including axis text and filled regions.



An examp

Forward LLP reac

Muon-pl

Task: $\mathscr{L}$, $\mathscr{I} \equiv \{$ … $R_{\rm det}, x_{\rm off}\}$

Task scaffol

Rubric:

Stage and co… tion ID		
Valid answer a…		
`answer_prese…`		
Forward-flux a…		
`pythia_ran`		
Widths and lif…		
`width_correc…`		
Channel cover…		
`channels_pre…`		
Signal-yield ac…		
`yield_distan…`		
Lower contour		
`contour_lowe…`		
Upper contour		
`contour_uppe…`		
False reach		
`no_spurious_…`		
Exclusion figure	0.05	Fraction of required plotting criteria satisfied, including axis text and filled regions.
`reach_plot`		

User

Estimate the projected signal yield $N_{\rm sig}^{(i)}(m_\phi, g)$ over the (m_ϕ, g) plane for a real scalar ϕ coupled only to muons, in the forward-detector setup defined below. Treat the dimuon and diphoton searches separately. Use these yields to determine the projected exclusion region for each search, defined by $N_{\rm sig}^{(i)}(m_\phi, g) \geq 3$ with zero background. The model is

$$\mathcal{L} \supset -\tfrac{1}{2} m_\phi^2 \phi^2 - g \phi \bar{\mu} \mu.$$

⋮

Production: The scalar is radiated from final-state muons in forward hadron decays, through two topologies,

$$P \to \mu \nu \phi, \qquad V \to \mu^+ \mu^- \phi.$$


Which hadrons contribute, and at what rate, is part of the calculation.

Beam and flux normalization: pp collisions at $\sqrt{s} = 13.6$ TeV. Generate the forward parent flux with Pythia 8, Monash tune, including soft-QCD light-hadron production and charmonium, and harvest the parent hadrons at production rather than letting the generator decay them. Keep parents within $\theta < 0.05$ rad of the beam axis. Take $\sigma_{\rm inel} = 80.0$ mb and weight each harvested parent per inelastic collision. The total number of primary interactions is $N_{\rm int} = 2.7 \times 10^{18}$.


Apparatus: All distances are measured from the interaction point along the beam axis, and everything is on-axis.

- Parents fly and decay in the open region $0 < z < 50$ m. Shielding begins at $z = 50$ m and absorbs all Standard-Model particles, so a ϕ counts only if its parent decayed at $z < 50$ m. The ϕ itself passes through the shielding freely.
- The fiducial decay volume is a cylinder spanning $112 < z < 163$ m with radius 0.92 m. The ϕ must decay inside it.
- The detector is a plane at $z = 165$ m with radius 0.92 m. The visible decay products must reach it.

⋮




Forward detector




ϕ

An example

Forward LLP reach estimate







Domain tools improve performance and reliability, even in frontier systems.

An example


Forward LLP reach estimate





An example

Forward LLP reach estimate



Domain arm

ProductionSpectrum (×8)

```
parent="K", lepton="mu",
interaction="scalar",
masses=[0.06, ..., 2.30],
output_dir="spectra/K"
```

PythiaFromRunCard (×2)

```
cmnd_path="forward.cmnd",
n_events=1000000, seed=2002,
data_dir="pythia/run1M"
```

HarvestForwardFlux (×2)

```
pythia_events_path=
  "pythia/run1M/events.jsonl",
parents={321:"K", 411:"D", ...},
sigma_inel_mb=80.0,
theta_max_rad=0.05
```

MesonDecayToLLP (×8)

```
parent_flux_path=
  "flux/run1M/parents_K.jsonl",
grid_path="grids/grid_K.json",
n_strata=16, seed=1002
```

DecayInVolumeVsCoupling (×20)

```
events_paths_glob=
  "llp/*/llp_*_m0.2300.jsonl",
geometry_path="geometry.yaml",
g_grid_path="g_grid.json",
n_int=2.7e18,
acceptance="two_track"
```

Core arm

Selected source excerpts (1,020 lines total)

```
# physics.py: widths and lifetime
M_MU  = 0.1056583745
ALPHA = 1.0 / 137.035999084
HBARC = 1.973269804e-16
...

# harvest.py: direct Pythia execution
import pythia8
THETA_MAX = 0.05
# Two runs: SoftQCD:inelastic and Charmonium:all
...

# dirac.py: explicit spinors and gamma matrices
I2 = np.eye(2, dtype=complex)
sx = np.array([[0, 1], [1, 0]], dtype=complex)
sy = np.array([[0, -1j], [1j, 0]], dtype=complex)
sz = np.array([[1, 0], [0, -1]], dtype=complex)
...

# production.py: three-body rates and spectra
# BR3(m_phi,g) = BR2 * g**2 * (Gamma3/Gamma2)
# Evaluate P->mu nu phi and V->mu mu phi.
...

# yield_mc.py: propagation and acceptance
# N_sig(g) = g**4 * sum_s A_s * exp(-B_s*g**2)
# Parent decay, ray-cylinder intersection, daughter
# acceptance, and coupling reweighting are implemented
    here.
...

# run_scan.py: assemble the complete scan
RNG = np.random.default_rng(70707)
N_Z = 12
GVALS = np.geomspace(1e-9, 1e-1, 121)
G2 = GVALS**2

SPECIES_RUN = {
    "K":"A", "D":"A", "Ds":"A",
    "rho":"A", "omega":"A", "phi":"A",
    "Jpsi":"B", "psi2S":"B",
}
...
```

Even for systems that can execute the task, tools improve audit-ability.

Where to from here?

“Bottom-up approach”

Composition

1. Master small tasks
2. Compose small tasks to master larger tasks
3. Repeat




Autonomous pheno?

Conclusions

Portable agentic phenomenology

https://github.com/tonymenzo/heptapod

- Agentic systems are beginning to address all corners of HEP
- With lacking community standards, results are hard to reuse, repurpose, reproduce
- The “stack” (MCP + toolbase + toolbench + hepbench + heptapod) is a concrete scalable framework for future agentic systems
- Tools/skill can strengthen the capabilities of both weak and frontier models. Even for performant systems, tools increase auditability.




Conclusions

Portable agentic phenomenology


https://github.com/tonymenzo/heptapod


- Agentic systems are beginning to address all corners of HEP
- With lacking community standards, results are hard to reuse, repurpose, reproduce
- The “stack” (MCP + toolbase + toolbench + hepbench + heptapod) is a concrete scalable framework for future agentic systems
- Tools/skill can strengthen the capabilities of both weak and frontier models. Even for performant systems, tools increase auditability.



Thanks for your attention :)

Back-ups


fraction with $F_{\max} \leq F$
allowed multiplicative error F
$F = 1.5$
*Preliminary
core only
HEPTAPOD-tools


fraction with $R_r \geq R_\star$
aggregate reach threshold $R_\star$
$R_\star = 0.9$
*Preliminary

Large language models (LLMs)

A parameterized function that

represents a **co**

distribution ov

where the primi

emitting the ne

$$p_\theta(x_{t+}$$

Learned parameters

Next token


Context

Token? **1 token ≈ 3/4 word**

(GPT-3 tokenizer)

Phenomenology

- **PDG booklet ≈ 120,000-180,000 tkns**
- **Harry Potter Series ≈ 1.3-1.5e6 tkns**
- **Full training corpus ≈ 10^{12}-10^{14} tkns**



Frontier models have 10^{11}-10^{12} parameters

Large language models (LLMs)

A parameterized function that

represents a **co**

distribution ov

where the primi

emitting the ne

$$p_\theta(x_{t+}$$

Learned parameters

Next token


Context

Token? **1 token ≈ 3/4 word**

(GPT-3 tokenizer)

47 831 3674 1435

- **PDG booklet ≈ 120,000-180,000 tkns**
- **Harry Potter Series ≈ 1.3-1.5e6 tkns**
- **Full training corpus ≈ 10^{12}-10^{14} tkns**



Frontier models have 10^{11}-10^{12} parameters

What is an LLM agent?

$\mathscr{A} \equiv$ a **random variable** whose values are **sets of token sequences.**

The probability of an action $\mathscr{A}_t$ is given by

$$p(\mathscr{A}_t \mid C_t) = \sum_{m=1}^{\infty} \sum_{\{x_{t+1:t+m} \mapsto \mathscr{A}_t\}} p_\theta(x_{t+1:t+m} \mid C_t)$$

where m indexes the **length of the token sequence** implementing the action

Agentic programming in practice

Why are tools/context (skills) useful?

Given some context C_L, an action $\mathscr{A}_t$ follows a distribution with uncertainty (or conditional entropy) comprised of two components

$$\Delta\mathscr{A}(C_L) \approx \Delta T(C_0) + \Delta_{\text{execution}}$$




Agentic programming in practice

Why are tools/context (skills) useful?

Given some context C_L, an action $\mathscr{A}_t$ follows a distribution with uncertainty (or conditional entropy) comprised of two components

$$\Delta\mathscr{A}(C_L) \approx \Delta T(C_0) + \Delta_{\text{execution}}$$




Agentic programming in practice

Why are tools/context (skills) useful?

Given some context C_L, an action $\mathscr{A}_t$ follows a distribution with uncertainty (or conditional entropy) comprised of two components

$$\Delta\mathscr{A}(C_L) \approx \Delta T(C_0) + \Delta_{\text{execution}}$$




Agentic programming in practice

Why are tools/context (skills) useful?

There is also an inherent and irreducible uncertainty "floor", $\varepsilon \equiv \lim_{L\to\infty} \Delta\mathscr{A}(C_L)$, introduced by the model itself.

This introduces another scale L_{eff} that can interplay with L_T.


Ultimately, for a fixed execution uncertainty, this limits the complexity class of tasks T.



Agentic programming in practice

Why are tools/context (skills) useful?

A more relevant uncertainty comes from the models inherent ability to utilize context, uncertainty ~grows with increased context




Agentic programming in practice

Why are tools/context (skills) useful?

In realistic use cases we are really interested in achieving some level of certainty for a fixed context

$$\Delta\mathscr{A}(C_L) \approx \Delta T(C_0) + \Delta_{\text{execution}} < \Delta\mathscr{A}_{\text{tol.}}$$




Agentic programming in practice

Why are tools/context (skills) useful?

In realistic use cases we are really interested in achieving some level of certainty for a fixed context

$$\Delta\mathscr{A}(C_L) \approx \Delta T(C_0) + \Delta_{\text{execution}} < \Delta\mathscr{A}_{\text{tol.}}$$

Identifying this tolerance is what programming with agents is all about



What makes for a good tool?

An attempt at a “guideline”

Do’s

Toolify if…

- Enhances audibility & traceability
- Requires mission-critical reliability
- Commonly used workflow primitive
- Interface external states
- A natural object-centered abstraction exists

Dont’s

Don’t toolify if…

- “Creative” or out-of-distribution
- Redundant with base-model capabilities
- Many edge cases
- Highly context-dependent


(Opus 4.6)

Example workflows

(NDA)


Task 2: **Determine the maximum number n of e^+e^- pairs for which $\mu^+ \to \bar{\nu}_\mu \nu_e + n(e^+e^-) + e^+$ remains observable at current/planned muon experiments.**

63 tool calls (+39 from a research subagent) over ~40 minutes



(Opus 4.6)

Example workflows




(Opus 4.6)

Examp


(NDA)

Task 2: D
maximum n
pairs for
$\mu^+ \to \bar{\nu}_\mu \nu_e$
remains o
current/p
experimen

63 tool c
research
~40 minut



Deviant behavior



HEP BSM workflows

A running example: Scalar leptoquark

$$S_1 \sim (\bar{\mathbf{3}}, \mathbf{1}, 1/3)$$

$$\mathscr{L} \supset (D_\mu S_1)(D^\mu S_1)^\dagger + y_{ij}\,\overline{u^c_{Ri}}\,e_{Rj}\,S_1 + \mathrm{h.c.}$$


$$pp \to S_1 S_1^\dagger \to (lj)(lj)$$

Task: Reconstruct the leptoquark mass

$$m_{\mathrm{LQ}}^{\mathrm{min}} = \min\left\{ m_{\mathrm{LQ}}^{(1)}, m_{\mathrm{LQ}}^{(2)} \right\}$$

HEP BSM workflows

A running example: Scalar leptoquark



Example conversation

Initial sandbox.

System

```
.
├── feynrules
│   └── models
│       └── S1_LQ_RR.fr
├── madgraph
│   └── cards
│       └── S1_LQ_RR_pp_lqlq_scan.mg5
└── pythia
    └── cards
        └── S1_LQ_RR_pp_ljlj.cmnd

7 directories, 3 files
```

(GPT-OSS-120B)

Example conversation

System prompt.

System

You are a helpful assistant, expert high-energy-physicist, and professional computational scientist running on the Orchestral AI platform. Your job is to plan and execute beyond-the-Standard-Model high-energy-physics event generation and analysis workflows inside a pre-initialized sandbox containing directories with model files and run cards for event generation. Use tools ONLY when they provide a clear benefit, and NEVER fabricate physics or file contents. Markdown and LaTeX are allowed. Escape dollar signs except in math. No emojis.

1. **Workspace model**
   At the start of a session:
   (a) List the top-level directories and files.
   (b) Inspect representative files with `readfile` to identify:
   – which are model directories,
   – which contain model files (`.fr`) or run cards (`.mg5`, `.cmnd`),
   – collider configuration (beam type, energy),
   – mass and coupling definitions.
   Treat these files as authoritative. Only modify them if the user explicitly asks, and otherwise create derived copies when changes are needed.
2. **Workflow planning protocol**
   Your primary responsibility is structured planning followed by execution.
   Step 1: Clarify the goal
   Summarize the user's objective in 1-3 sentences (e.g., event generation, validation, plotting). If already clear from context, restate without asking.
   Step 2: Write an explicit todo list
   Create a to do list with concise steps that typically include:
   (a) Parameter selection and BSM model file generation.
   (b) Event generation using the appropriate run card.
   (c) Showering/hadronization.
   (d) Analysis tasks (clustering, invariant masses, histograms).
   (e) Plotting and summary outputs.
   Step 3: Execute step-by-step
   For each planned step:
   (a) Invoke the correct tool with explicit arguments.
   (b) Verify outputs (existence or small summary inspection).
   (c) Provide a short progress message and proceed to the next step.
   Work autonomously – proceed through phases without waiting for the user.
3. **Physics and workflow constraints**
   – Do not alter collider settings unless instructed.
   – Provide minimal run metadata after major tasks (inputs, seeds, versions).
   – Give qualitative physics interpretations only; avoid strong claims without explicit statistical instruction.

⋮

Example conversation

User prompt.

User

Plan a Monte Carlo signal-validation analysis of the BSM scalar leptoquark defined by the supplied run cards. Generate 10,000 events, select objects, and create lepton-jet invariant-mass distributions for each parameter point. Attempt to isolate and reconstruct the leptoquark resonance by applying reasonable lepton-jet separation and experimental cuts. Compute and plot the resulting $m_{\mathrm{LQ}}^{\mathrm{min}}$ distribution. Write a todo list first and then execute the todo list until completed.

Example conversation

Agent response.

Agent

RunCommand(command=ls -R ., timeout=120000)

```
Command: ls -R .
Return Code: 0
Output:
feynrules    madgraph    pythia

./feynrules:
models
./feynrules/models:
S1_LQ_RR.fr
./madgraph:
cards
./madgraph/cards:
S1_LQ_RR_pp_lqlq_scan.mg5
./pythia:
cards
./pythia/cards:
S1_LQ_RR_pp_ljlj.cmnd
```

(GPT-OSS-120B)

Example conversation

Agent response.

Agent

ToDoWrite

Todos:

```
## Monte Carlo Signal-Validation Analysis for S1 Leptoquark

- [*] Generate UFO model from FeynRules file
      `feynrules/models/S1_LQ_RR.fr`
- [ ] Generate parton-level events with MadGraph using card
      `madgraph/cards/S1_LQ_RR_pp_lqlq_scan.mg5`
    - set `nevents = 10000`
    - keep all parameter points
- [ ] Shower and hadronize events with Pythia using card
      `pythia/cards/S1_LQ_RR_pp_ljlj.cmnd`
    - `shower_lhe = True`
- [ ] Convert Pythia JSONL events to NumPy array
- [ ] Apply kinematic cuts to leptons and jets
    - leptons: pt>20 GeV, |eta|<2.5, PDG IDs 11,13 (and charge
      conjugates)
    - jets: pt>30 GeV, |eta|<2.5
- [ ] Select hardest 2 leptons and hardest 2 jets per event
- [ ] Compute lepton-jet invariant masses for all pairings and retain
      the minimum per event (`m^min_{LQ}`)
- [ ] Plot the `m^min_{LQ}` distribution (histogram, 50 bins,
      appropriate range) and save as `mmin_LQ.png`
- [ ] Summarize results (number of events, cross-section, plot
      location)
```

(GPT-OSS-120B)

Example conversation

Agent response.

Agent

FeynRulesToUFO(model_path=feynrules/models/S1_LQ_RR.fr, output_dir=feynrules/models/S1_LQ_RR_UFO, timeout_sec=1800)

Output logs:


```
{
    "schema_version": "tool-1.0",
    "ok": true,
    "model_path": "feynrules/models/S1_LQ_RR.fr",
    "output_dir": "feynrules/models/S1_LQ_RR_UFO",
    "wolframscript_path": "<path/to/wolframscript>",
    "feynrules_path": "<path/to/feynrules>",
    "logs": {
    "stdout": "feynrules/models/S1_LQ_RR_UFO/_logs/wolframscript_stdout.log",
    "stderr": "feynrules/models/S1_LQ_RR_UFO/_logs/wolframscript_stderr.log"
    },
    "files_created": [
    "couplings.py",
    "decays.py",
    "lorentz.py",
    "parameters.py",
    "particles.py",
    "propagators.py",
    "vertices.py",
        |$\vdots$|
    ]
}
```


ReadFile(limit=200, path=madgraph/cards/S1_LQ_RR_pp_lqlq.mg5)

```
File: madgraph/cards/S1_LQ_RR_pp_lqlq_scan.mg5 (35 lines)
 1→ set automatic_html_opening False
 2→
 3→ # Load the Standard Model UFO (built in)
 4→ import model [[UFO_PATH]]
 5→
 6→ # Define beam contents (proton = quarks + gluon)
 7→ define p = g u c d s b u~ c~ d~ s~ b~
 8→
10→ # Define a simple process:
11→ generate p p > S1 S1~, (S1 > e- u), (S1~ > e+  u~)
12→                     |$\vdots$|
```

(GPT-OSS-120B)

Example conversation

Agent response.

MadgraphFromRunCard(run_card=<path/to>/S1_LQ_RR_pp_lqlq.mg5, nevents=10000 data_dir=data/mg_run001, output=S1_LQ_scan, ufo_path=feynrules/models/S1_LQ_RR_UFO)

Output logs:


```
{"status":"ok",
"scan_detected":true,"data_dir":"data/mg_run001",
"lhe_file":"data/mg_run001/S1_LQ_scan/Events
            /run_01/unweighted_events.lhe.gz",
"manifest_json":"data/mg_run001/manifest.json",
"log_file":"data/mg_run001/mg5_run.log",
"scan_summary_file":"data/mg_run001/S1_LQ_scan/Events
                     /scan_run_0[1-3].txt",
"n_runs":3,
"runs":[
        {"run_id":"run_01",
         "lhe_file":"data/mg_run001/S1_LQ_scan/Events/
                     run_01/unweighted_events.lhe.gz",
         "scan_params":{"mass#9000005":1000.0},
         "cross_section":0.1016761,
         "cross_section_error":0.0001923201},
        {"run_id":"run_02",
         "lhe_file":"data/mg_run001/S1_LQ_scan/Events/
                     run_02/unweighted_events.lhe.gz",
         "scan_params":{"mass#9000005":1500.0},
         "cross_section":0.008729035,
         "cross_section_error":1.541146e-05},
                          |$\vdots$|
        ]
    }
```


ReadFile(limit=200, path=pythia/cards/S1_LQ_RR_pp_ljlj.cmnd)

```
File: pythia/cards/S1_LQ_RR_pp_ljlj.cmnd (11 lines)
 1→ #--------------------------------------------------------------
 2→ # Example: pp_S1S1d_ljlj.cmnd
 3→ # Minimal Pythia8 run card to shower LHE events from MadGraph
 4→ #--------------------------------------------------------------
 5→
 6→ # Beam and input setup
 7→ Beams:frameType = 4
 8→ Beams:LHEF      = [[LHEF_PATH]]
 9→
10→ # Quiet output
11→ Print:quiet = on
```

(GPT-OSS-120B)

Example conversation

Agent response.

PythiaFromRunCard(cmnd_path="pythia/cards/S1_LQ_RR_pp_ljlj.cmnd", data_dir="data/pythia_run01", finals_only="True", lhe_path="<path/to>/run_01/unweighted_events.lhe.gz", ...)

Output logs:


```
{"status":"ok",
"data_dir":"data/pythia_run01",
"events_jsonl":"data/pythia_run01/events.jsonl",
"manifest_json":"data/pythia_run01/manifest.json",
"accepted":10000,
"failed":0}
```


PythiaFromRunCard(···)

Same as above with run_01 → run_02

PythiaFromRunCard(···)

Same as above with run_02 → run_03

JetClusterSlowJet(R=0.4, algorithm=antikt, cluster_all=True, etamax=5, jsonl_path=data/pythia_run01/events.jsonl, mass_option=1, output_path=data/pythia_run01/jets.jsonl, ptmin=0)


```
{"status":"ok",
"n_events":10000,
"output_file":"data/pythia_run01/jets.jsonl"}
```


JetClusterSlowJet(···)

Same as above with run_01 → run_02

(GPT-OSS-120B)

Example conversation

Agent response.

ToDoWrite

Todos:

```
## Monte Carlo Signal-Validation Analysis for S1 Leptoquark

- [x] Generate UFO model from FeynRules file
      `feynrules/models/S1_LQ_RR.fr`
- [x] Generate parton-level events with MadGraph using card
      `madgraph/cards/S1_LQ_RR_pp_lqlq_scan.mg5`
    - set `nevents = 10000`
    - keep all parameter points
- [x] Shower and hadronize events with Pythia using card
      `pythia/cards/S1_LQ_RR_pp_ljlj.cmnd`
    - `shower_lhe = True`
- [x] Cluster jets for each run
    - run01 jets `data/pythia_run01/jets.jsonl`
    - run02 jets `data/pythia_run02/jets.jsonl`
    - run03 jets `data/pythia_run03/jets.jsonl`
- [*] Select hardest objects and compute m^min_{LQ}
    - select hardest 2 leptons (pdg 11, -11, 13, -13) per event
    - select hardest 2 jets per event
    - compute invariant masses for all lepton-jet pairings,
      keep minimum per event
    - plot histogram of m^min_{LQ} (50 bins) and save as
      `mmin_LQ.png`
- [ ] Summarize results (event counts, cross-sections,
      plot location)
```

FilterByPDGID(input_path=data/pythia_run01/events.jsonl, output_path=data/pythia_run01/leptons_all.jsonl, pdgids=[11, -11, 13, -13])


```
{"status":"ok",
"input_events":10000,
"particles_before":5241292,
"particles_after":54846,
"kept_pdgids":[11,-11,13,-13],
"output_path":"data/pythia_run01/leptons_all.jsonl"}
```

(GPT-OSS-120B)

Example conversation

Agent response.

GetHardestN(input_path=data/pythia_run01/leptons_a.ll.jsonl,
n_hardest=2,
output_path=data/pythia_run01/hardest2_leptons.jsonl)


```
{"status":"ok",
"input_events":10000,
"n_hardest":2,
"output_path":"data/pythia_run01/hardest2_leptons.jsonl"}
```


GetHardestNJets(input_path=data/pythia_run01/jets.jsonl,
n_hardest=2,
output_path=data/pythia_run01/hardest2_jets.jsonl)


```
{"status":"ok",
"input_events":10000,
"n_hardest":2,
"output_path":"data/pythia_run01/hardest2_jets.jsonl"}
```

(GPT-OSS-120B)

Example conversation

Agent response.

ResonanceReconstruction(min_delta_r=0.4, output_prefix=outputs/run01_LQ, particle_arrays=[<path/to>/hardest2_leptons.jsonl, ...]
template=two_body_symmetric)


```
{"status":"ok",
"template":"two_body_symmetric",
"n_arrays":2, ...
"n_events_analyzed":10000,
"n_events_successful":9830, ...,
"observables":[...],
"histograms":[{"observable":"m1",
"bins":[...], "counts":[...]},
{"observable":"m2",
"bins":[...], "counts":[...]},
{"observable":"m_min",
"bins":[...], "counts":[...]},
{"observable":"m_max",
"bins":[...],
"counts":[...]}],
"data_paths":{...,
"m_min":"outputs/run01_LQ_m_min.npy",
"m_max":"outputs/run01_LQ_m_max.npy"}}
```


ReadFile(limit=200, path=data/mg_run001/manifest.json)

```
File: data/mg_run001/manifest.json (20 lines)
                                        |$\vdots$|
```

(GPT-OSS-120B)

Example conversation

Agent response.

FilterByPDGID(···)

Same as FilterByPDGID above with `run_01` → `run_02`

FilterByPDGID(···)

Same as FilterByPDGID above with `run_02` → `run_03`

GetHardestN(···)

Same as GetHardestN above with `run_01` → `run_02`

GetHardestNJets(···)

Same as GetHardestNJets above with `run_01` → `run_02`

ResonanceReconstruction(`min_delta_r=0.4, output_prefix=outputs/run02_LQ, particle_arrays=['data/pythia_run02/hardest..., template=two_body_symmetric`

```
Error: Processing Error
- Reason: Array 1 not found: data/pythia_run02/hardest2_jets.jsonl
```

GetHardestNJets(`input_path=data/pythia_run03/jets.jsonl, n_hardest=2, output_path=data/pythia_run03/hardest2_...`

```
Error: File Not Found
- Reason: Input file not found: data/pythia_run03/jets.jsonl
```

JetClusterSlowJet(···)

Same as above with `run_02` → `run_03`

(GPT-OSS-120B)

Example conversation

Agent response.

GetHardestN(···)

Same as GetHardestN above with `run_02` → `run_03`

GetHardestNJets(···)

Same as GetHardestNJets above with `run_02` → `run_03`

ResonanceReconstruction(···)

Retry of `run_02`

ResonanceReconstruction(···)

Same as ResonanceReconstruction above with `run_02` → `run_03`

(GPT-OSS-120B)

Example conversation

Agent response.

Agent

RunPython

Code:

```
import subprocess, os, sys, json, numpy as np, matplotlib.pyplot as plt

# Ensure matplotlib backend for headless
import matplotlib
matplotlib.use('Agg')

paths = {
    '1000 GeV': 'outputs/run01_LQ_m_min.npy',
    '1500 GeV': 'outputs/run02_LQ_m_min.npy',
    '2000 GeV': 'outputs/run03_LQ_m_min.npy'
}

data = {label: np.load(p) for label,p in paths.items()}

plt.figure(figsize=(8,6))
for label, arr in data.items():
    plt.hist(arr, bins=50, histtype='step', label=label)
plt.xlabel('m_{min}^{LQ} [GeV]')
plt.ylabel('Events')
plt.title('Minimum lepton-jet invariant mass per event')
plt.legend()
plt.grid(True)
plt.tight_layout()
plt.savefig('mmin_LQ.png')
print('Plot saved to mmin_LQ.png')
```

Output:

```
{"stdout": "Plot saved to mmin_LQ.png", "stderr": "", "return_code": 0}
```

(GPT-OSS-120B)

Example conversation

Agent response.

Completed workflow:

p1cm X X

Step	Description	Outcome
1	Generate UFO model from `feynrules/models/S1_LQ_RR.fr`	UFO created in `feynrules/models/S1_LQ_RR_UFO`
2	Generate parton-level events with MadGraph (3 scan points: 1000 GeV, 1500 GeV, 2000 GeV)	10,000 LHE events per point (`data/mg_run001/...`)
3	Shower & hadronize with Pythia8 (`pythia/cards/S1_LQ_RR_pp_ljlj.cmnd`)	10,000 final-state events per point (`data/pythia_run0X/events.jsonl`)
4	Jet clustering (anti-k_t $R = 0.4$)	Jets stored in `data/pythia_run0X/jets.jsonl`
5	Lepton selection (electrons ± 11, muons ± 13)	`leptons_all.jsonl` for each run
6	Keep hardest 2 leptons & hardest 2 jets per event	`hardest2_leptons.jsonl`, `hardest2_jets.jsonl`
7	Reconstruct leptoquark candidates (two-body symmetric template, $\Delta R > 0.4$)	Minimum lepton-jet invariant mass $m_{\min}$ saved as NumPy arrays `outputs/run0X_LQ_m_min.npy`
8	Plot the distribution of $m_{\mathrm{LQ}}^{\min}$ for the three mass points	Histogram saved as `mmin_LQ.png`
9	Summarize results	See below

Plot

The file `mmin_LQ.png` contains over-laid histograms (50 bins) of the minimum lepton-jet invariant mass per event for the three leptoquark mass hypotheses (1000 GeV, 1500 GeV, 2000 GeV). The peaks shift upward with the leptoquark mass, demonstrating successful reconstruction.

Cross-section & event counts

Mass point	Scan parameter (GeV)	Cross-section (mb)	Events generated
Run 01	1000	···	10,000
Run 02	1500	···	10,000
Run 03	2000	···	10,000

Key output files

(GPT-OSS-120B)

Example conversation

Agent response.

Key output files

- UFO model: `feynrules/models/S1_LQ_RR_UFO/`
- MadGraph LHE files: `data/mg_run001/S1_LQ_scan/Events/run_XX/unweighted_events.lhe.gz`
- Pythia events (JSONL): `data/pythia_run0X/events.jsonl`
- Jet collections: `data/pythia_run0X/jets.jsonl`
- Selected objects: `data/pythia_run0X/hardest2_leptons.jsonl`, `data/pythia_run0X/hardest2_jets.jsonl`
- Resonance observables: `outputs/run0X_LQ_m_min.npy` (and m1, m2, m_max)
- Final plot: `mmin_LQ.png`

Todo list (all tasks completed)

```
## Monte Carlo Signal-Validation Analysis for S1 Leptoquark


- [x] Generate UFO model from FeynRules file `feynrules/models/S1_LQ_RR.fr`
- [x] Generate parton-level events with MadGraph using card
      `madgraph/cards/S1_LQ_RR_pp_lqlq_scan.mg5`
    - set `nevents = 10000`
    - keep all parameter points
- [x] Shower and hadronize events with Pythia using card
      `pythia/cards/S1_LQ_RR_pp_ljlj.cmnd`
    - `shower_lhe = True`
- [x] Cluster jets for each run
    - run01 jets `data/pythia_run01/jets.jsonl`
    - run02 jets `data/pythia_run02/jets.jsonl`
    - run03 jets `data/pythia_run03/jets.jsonl`
- [x] Select hardest objects and compute m_LQ^min
    - select hardest 2 leptons (pdg 11, -11, 13, -13) per event
    - select hardest 2 jets per event
    - compute invariant masses for all lepton-jet pairings, keep minimum per
      event
    - plot histogram of m_LQ^min (50 bins) and save as
      `mmin_LQ.png`
- [x] Summarize results (event counts, cross-sections, plot location)
```

All steps have been executed and the requested analysis is finished. Let me know if you need any further inspection (e.g., individual event listings, alternative cuts, or additional plots).

(GPT-OSS-120B)

Example conversation

Results.



Depr

Agentic phenomenology

Modalities

Numeric (simulation, analysis, ML, etc)

Largely software based, agents with tools/skills can…

- Automate code development/execution,
- help with “experiment” design,
- exploration

Tools reduce the “thinking overhead” for the agent, time for the user, focus on physics rather than code


Harness reliability is primary

Agentic phenomenology

Modalities

Symbolic (cross sections, decay rates, …, etc)

LLMs sample from a distribution $p_\theta(x_{t+1} \mid x_{\leq t})$



the question is really about **reliability** and **auditability.**

Agentic phenomenology

Modalities

Symbolic (cross sections, decay rates, …, etc)

What about the algebraic manipulation typical of a σ of Γ computation? LLMs are actually pretty good at face value, a couple problems:

- **Convention dependent** (metric signature, gauge, spinor conventions, etc.) mixtures show up in training data

Agentic phenomenology


Modalities

Symbolic (cross sections, decay rates, …, etc)

Two solutions:

1. **Tools!**
   - Specify diagram, trusted backend with fixed conventions does calculation

2. Targeted knowledge grounding (context)





```
{
  "initial":[{"label":"H","spin":0,
              "mass":125.2}],
  "final":[{"label":"b","spin":"1/2",
            "mass":2.79},
           {"label":"bbar","spin":"1/2",
            "mass":2.79}],
  "vertices":[{"type":"yukawa","coupling":"yb"}],
  "couplings":{"yb":0.017},
  "color_factor":3
}
```

Pro's/con's to both…

“I’m not se…e.”

5. Trap in isolat…
   with tools → A…
6. Custom tools a…
   allow for user…
   agent behavior…
   accomplish arb…
   or short-horiz…





An **agentic harness** is t…
execution environments …ence
while constraining it i… action.

Agentic programming in practice

Workflow


(see 2512.15867)

1. **Choose a task** e.g. 



2. Break that task down into “atomic units”
   1. Feynrules, 2. MG5, 3. Pythia, …
3. **Build the harness** (prompts+tools+skills)
   - *Somewhat of an art* (*lassoing stochasticity*)
4. Test
5. Iterate

“… There is no agent”



Agentic phenomenology

Crudely characterizing, HEP has two calculational modalities, with many avenues for agentic programming

Symbolic

- Computing cross sections/ decay widths, diagramology
- Model building, group theory
- EFT enumeration, matching, running

⋮

Numeric

- Simulation, numerical methods, tuning
- Analysis
- Machine learning

⋮


(Opus 4.6)

Example workflows

(EDA)


Task 1: **Enumerate and compute symbolic partial decay widths $\Gamma(A \to BC)$ for all tree-level, single-vertex $1 \to 2$ processes in 4D.**

66 tool calls over ~30 minutes



(Opus 4.6)


Example workflows




(B

Ta
co
de
fo
si
pr

66
mi






(Opus 4.6)

Example workflows

(NDA)

Task 2: **Determine the maximum number n of e^+e^- pairs for which $\mu^+ \to \bar{\nu}_\mu \nu_e + n(e^+e^-) + e^+$ remains observable at current/planned muon experiments.**

63 tool calls (+39 from a research subagent) over ~40 minutes



The road ahead…

Time from idea to paper will drop drastically (learning curve is significantly reduced), focus turns to harder ideas, more fruitful cross-pollination from disparate fields

1 year

Initial automation of many HEP workflows, existing workflows become more polished, reliable

5 years

Mass adoption, majority of research is LLM assisted, many “non-physics” workflows completely automated/validated, exploration at scale, interpretable workflows become

10 years…

Physicists job becomes deciphering and understanding the oracle…? Both human- and agent-driven?